

# Aluminum Dump Bodies

Alumatech<sup>®</sup>, Vertex<sup>®</sup> & The Wave<sup>®</sup>

# OX BODIES<sup>®</sup>



**“As Strong As An Ox”**

*Subsidiary of Federal Signal Corporation*

## Alumatech<sup>®</sup> Specifications

|                 |                            |
|-----------------|----------------------------|
| Body Type/Width | Half Round                 |
| Body Length     | 13'-26'                    |
| Side Height     | 57", 60", 63", 66" or 69"  |
| Floor Sheet     | .250 5454 H34 Alum.        |
| Side Wall       | .190 5454 H64 Alum.        |
| Top Rail        | 10"x6" A-T6                |
| Nose Panel      | .250 Aluminum              |
| Tailgate        | Sealed, Air Actuated Latch |
| Rear Apron      | Alum. Length Optional      |
| Weight          | 2120 lbs. (14' x 57")      |

## ALUMATECH<sup>®</sup>

The Alumatech's<sup>®</sup> half-round seamless design combines strength and style for the optimal body to fit your material hauling needs. The Alumatech<sup>®</sup> releases loads at a lower dump angle and centers the load, reducing the chance of turnover caused by one-side loading. With aerodynamic, fuel-saving smooth sides and aluminum weight savings, the Alumatech<sup>®</sup> offers cost savings load after load.



All bodies shown with some optional equipment.  
Models and options are subject to change without notice.



**OX BODIES MANUFACTURING, INC.**

1-800-648-1101 | Fax: 205-932-2594

www.oxbodies.com | Email: sales@oxbodies.com

**SOLD BY**

All bodies come standard with a single-acting front-mount telescopic hoist.

### Available options for all bodies:

- Two-Way/Barn Door Tailgate
- Air Lift Tailgate (Not Available on Alumatech<sup>®</sup>)
- Hi-Lift Tailgate
- Coal/Grain Door Tailgate
- Rigid or Folding Ladder
- Narrow (24"x65") or Full-Width (24"x96") Cabshield
- 8", 10", 12" or 16" Apron
- 6"-12" Board Pockets
- Insulation (Wave<sup>®</sup> and Vertex<sup>®</sup>)

The Wave® and the Vertex® are dual threats with their patented dual-wall polished extrusions made of strong, long-lasting aluminum. Their walls are surprisingly thin without compromising on toughness. The polished outer walls give the bodies a distinctive look, while sturdy inner walls and stiffeners hide dents and dings. The Wave® and the Vertex® feature aerodynamic, fuel-saving sides; water-tight, rubber seal tailgates; and patented SST-shaped crossmembers for optimal performance in the field.

**The Wave® Specifications**

|                        |   |
|------------------------|---|
| <b>Body Type/Width</b> | 96"   |
| <b>Body Length</b>     | 14'-21' (1-ft. Increments Only)   |
| <b>Side Height</b>     | 48", 54", 60" or 66"  |
| <b>Floor Sheet</b>     | .250 5454 H34 Alum.   |
| <b>Side Wall</b>       | Horizontal Dual Wall 6005 A-T6 Alum Extrusion 2¾" Hollow Core with Inner Stiffeners |
| <b>Top Rail</b>        | Rounded ½" Thick "Bullnose"   |
| <b>Rub Rail</b>        | 6"x3" Tube  |
| <b>Nose Panel</b>      | .250" 5454 H32  |
| <b>Tailgate</b>        | Wave® Sealed Air Operated   |
| <b>Floor Supports</b>  | 5.5" SST Cross Beams Full-Length Longitudinal                                       |
| <b>Steps</b>           | Driver's Side Cast  |
| <b>Rear Apron</b>      | Alum. Length Optional   |



|                        |  |
|------------------------|--|
| <b>Body Type/Width</b> | 96"  |
| <b>Body Length</b>     | 14'-21' (1-ft. Increments Only)  |
| <b>Side Height</b>     | 48"-66"  |
| <b>Floor Sheet</b>     | .250 5454 H34 Alum.  |
| <b>Side Wall</b>       | Vertical Dual Wall 6005 A-T6 Alum. Extrusion 2¾" Hollow Core with Inner Stiffeners |
| <b>Top Rail</b>        | 7" tall x 4.5" wide  |
| <b>Rub Rail</b>        | 4"x6" Boxed  |
| <b>Nose Panel</b>      | .250" 5454 H32   |
| <b>Tailgate</b>        | Sealed, Air Operated Latch   |
| <b>Floor Supports</b>  | 7"x5" Bucket Shape   |
| <b>Rear Apron</b>      | Alum. Length Optional  |
| <b>Weight</b>          | 2560 lbs. (14' x 48")  |

**Vertex® Specifications**