

## CHISHOLIM





www.OXBODIES.com



## For demolition, riprap, asphalt, salt, sand-to-large aggregates, spreading materials, on and off road applications



Optional tailgate coal chute (maximum of three).



Optional 12" to 42" cab shields (fixed on bolt on).



Exterior ladder/interior rungs front driver's side.



Optional side mounted hydraulic tank with site glass.



Recessed and rubber grommeted LED lighting to meet FMVSS 108.



Optional steel or Tread Brite aluminum gravel guards.

Optional

Two-way barn

door tailgate



## CHISHOLM BASE OPTIONS

for the Chisholm™

- Sloped front gate with external hoist well
- Commercial grade 3/16" AR400 Hardox steel (front gate, side, tailgate)
- Commercial grade 3/16", 3/8", or 1/2" AR400 Hardox steel (floor)
- 4" x 4" x 1/4" square tubing Diamond Mount top rail
- 10 gauge steel cab shield in 12", 24", 36", or 42" lengths in several widths (fixed or bolt-on)
- 6" or 12" sloped tailgate
- Two-way barn door, double acting, high lift, or High 'N Slide tailgate
- 1/4" plate or heavy duty 1/4" plate (schedule 80) apron 6"-12" in 2" increments
- Cross-memberless steel, 8" or 10" I-Beam longsill
- Controls: all air, hot shift PTO or any combination
- Electric brake control
- Front, above frame, or side mounted hydraulic tanks with site glass
- Hoist options up to 8" diameter (Standard or Chrome)
- Heat diverter, manual or automatic
- Heated floor, floor strip, or floor panels
- Manual or electric flip or side roll tarps in mesh or vinyl

- Multiple side board options in (Metal, aluminum, wood or composite)
- Dirt-shedding angles for sides, tailgate, and hoist well
- Hinged and non-hinged ladder options available
- Tailgate coal chute (maximum of three)
- Sealed tailgate factory installed or kit
- Recessed and rubber grommeted LED additional side and rear facing lighting to meet FMVSS 108
- Body liners in 1/4", 3/8", or 1/2" thickness
- Flat steel lower walk/tarp tie down strip
- Tread Brite aluminum bottom rail covers
- Steel or aluminum Tread Brite gravel guards
- Retractable or air-operated flip up anti-sail mud flaps
- Under body vibrator
- Spreader bar
- Pintle hitches to 50 ton
- Lift axles in 8K, 10K, 13.2K, or 20K steerable, or 20K rigid for most body lengths 16' to 21'
- Steel & Aluminum wheels in various sizes and multiple tire configurations on Ox installed lift axles -
- All-weather package (includes continuous weld. chrome hoist, and 2-year warranty)
- Custom paint colors









719 Columbus Street East • Fayette, AL 35555 Phone 205-932-5720 • 800-844-2519

Photos are representative only, actual product may vary.

Authorized Ox Bodies Dealer





©2015 Ox Bodies