

www.OXBODIES.com







Optional Full body height exterior and internal ladder located on front driver's side.



Drop-leg landing gear.



Cross-memberless, 10" I-Beam longsill frame design with Flex Inhibitors.
(Elliptical "U" & "J" only)



Recessed and rubber grommet mounted LED lighting for side body, tail, clearance, and backup lights to meet Federal standard 108.

Trailox QUARTER FRAME SQUARE BOTTOM "L" BODY

The Square Bottom "L" Body has the features of the Elliptical "U" and "J" Bodies with these key differences.

- 17 39.8 Cubic Yard Capacity
- Stacked, 4" structural cross-members, 6" I-Beam longsill frame design.
- Vertical line posts with 10 gauge hightensile steel sides.
- Commercial grade 10 gauge high-tensile steel used for sides with 3/16" hightensile steel floor. (Also on "J" Body)
- 3/16" high-tensile steel floor.



Trail Ox BASE OPTIONS

for Elliptical "U" Body, "J" Body & Square Bottom "L" Body

- Body width of 102".
- 1/4" Hardox AR450 steel used for sides. (Elliptical "U" only)
- Multiple material choices available for floor plate and tailgate. (Elliptical "U" only)
- Multiple material choices available for sides, floor plate and tailgate. (Square Bottom "L" and "J" Body only)
- Sloped front with external hoist mount in 3/16" or 1/4" AR450 Hardox steel.
- Stacked, I-Beam cross-member with 6" I-Beam longsill frame design. (Square Bottom "L" only)
- Two way, side swing, and High-Lift (shown) tailgate options available.
- Tailgate coal chute (maximum of three).
- Sealed tailgate kit.
- Dirt-shedding angle available for side top rail, tailgate, and hoist well.
- Recessed and rubber grommet mounted LED additional side and rear facing lighting in rear posts to meet Federal 108 are also available.
- In-cab wet line system with mounted control panel for hoist, tailgate, and tarping system.

- Additional air tank for increased capacity.
- Under body vibrator.
- Rubber flaps with anti-sail brackets or steel gravel quards for mount in front of suspension.
- Air ride tandem axle available for all body lengths.
- Air ride tri-axle available. (28' Elliptical "U" and Square Bottom "L" bodies only)
- Lift axles in 13.5K or 20K steerable, or 20K rigid for 28' length. (Elliptical "U" and Square Bottom "L" bodies only)
- 4S/2M ABS braking system.
- Steel disc wheels in 22.5 x 8.25 or 24.5 x 8.25 in multiple tire configurations.
- Aluminum disc wheels in 22.5 x 8.25 or 24.5 x 8.25 in multiple tire configurations.
- 2-speed landing gear
- Semi-auto or electric flip tarps, cable systems, or side roll tarps with choice of mesh or vinyl covers.
- 6" or 8" side boards in metal or wood.
- Custom paint colors.







TRAILERS

"As Strong As An Ox" ®

719 Columbus Street East • Fayette, AL 35555 Phone 205-932-5720 • 800-844-2519 www.oxbodies.com

Authorized Ox Bodies Dealer



