

TrailOx FULL FRAME ELLIPTICAL "U" BODY



Dimensions - "U" and "L" body

- 96" Wide
- Lengths of 24'-36'
- Side heights of 36"-60" (in 6" increments)

DETPARLETS

- Tailgate height 6" higher than sides
- 18 51.2 Cubic Yard Capacity (Elliptical "U" only)
- Continuous seam-welded design reduces debris collection and weather-related body corrosion.
- Rubber flaps, front corner mounted
- 36" anti-sail, rear rubber mud flaps.
 - Conventional 7 gauge high-tensile steel, air operated tailgate.

• 2 year warranty on body and chassis.

Steel, 16" x 26# wide flange I-Beam chassis.



 Epoxy primer and polyurethane top coated body. Body available in four standard colors. Chassis standard color is black.









 Heavy-duty frame-to-body hinges with 2-1/2" diameter CR pin and 1/8" NPT grease zerks.

- Single point- tandem suspensions.
- Commercial grade 3/16" Hardox AR450 steel used for sides with 1/4" Hardox AR450 for floor. (Elliptical "U" only)
- 3/16" high-tensile steel bulkhead and hoist well.



"As Strong As An Ox"™



Trail Ox Series Elliptical





for both Elliptical "U" Body & Square Bottom "L" Body

BASE OPTIONS

- . Body width of 102".
- 1/4" Hardox AR450 steel used for sides. (Elliptical "U" only)
- Multiple material choices available for tailgate. (Elliptical "U" only)
- Multiple material choices available for sides, floor plate and tailgate. (Square Bottom "L" only)
- Sloped front with external hoist mount in 3/16" or 1/4" AR450 Hardox steel.
- Stacked, I-Beam cross-member with 6" I-Beam longsill frame design. (Square Bottom "L" only)
- Steel, 16" x 31# or 18" x 35# wide flange I-beam chassis.
- High-Lift tailgate option available.
- Tailgate coal chute.
- Sealed tailgate kit.
- Dirt-shedding angle available for side top rail, tailgate, and hoist well.
- Recessed and rubber grommet mounted LED additional side and rear facing lighting in rear posts to meet Federal 108 are also available.
- In-cab wet line system with mounted control panel for hoist, tailgate, and tarping system.

- 9" diameter, telescoping hoist for body lengths of 30' thru 36'.
- Additional air tank for increased capacity.
- Under body vibrator.
- Rubber flaps with anti-sail brackets or steel gravel guards for mount in front of suspension.
- Tandem single point, mechanical tri-axle, air ride tandem axle available for all body lengths. (Square Bottom "L" only)
- Air ride tri-axle available for 28' thru 36' lengths. (Elliptical "U" only)
- Lift axles in 13.5K or 20K steerable, or 20K rigid for body lengths of 28' thru 36' feet.
- Air ride tandem axle available for all body lengths. (Elliptical "U" only)
- 4S/2M ABS braking system.
- Steel disc wheels in 22.5 x 8.25 or 24.5 x 8.25 in multiple tire configurations.
- Aluminum disc wheels in 22.5 x 8.25 or 24.5 x 8.25 in multiple tire configurations.
- Semi-auto or electric flip tarps, cable systems, or side roll tarps with choice of mesh or vinyl covers. ——
- 6" or 8" side boards in metal or wood.
- Custom paint colors.









719 Columbus Street East • Fayette, AL 35555 Phone 205-932-5720 • 800-844-2519 Authorized Ox Bodies Dealer



